

Unleaded 95	Testing method	SN EN 228 SN 181 162	Average values
Density at 15°C	kg/m ³	ISO 3675	min. 720 max. 775 745
<i>Reid vapour pressure at 37.8°C</i>			
Summer quality (class A)	kPa	EN 12	45 - 60
Winter quality (class E/E1)	kPa		60 - 90 60 - 90
Boiling analysis			
<i>Evaporated quantity at 70°C, E70</i>			
Summer quality	Vol. %		20 - 48
Winter quality	Vol. %		22 - 50 22 - 50
<i>Evaporated quantity at 100°C, E100</i>			
Summer quality	Vol. %		46 - 71
Winter quality	Vol. %		46 - 71 46-71
<i>Evaporated quantity at 150°C, E150</i>			
Summer quality	Vol. %		min. 75
Winter quality	Vol. %		min. 75 min 75
Final boiling point (FBP)	°C		max 210 max 210
Distillation residue	Vol. %		max. 2 < 1
<i>Vapour lock index VLI (VLI = 10RVP + 7E70)</i>			
Summer quality		--	
Winter quality (April and October)		max. 1150	<1150
Sulphur content	mg/kg	ISO 14596	max. 10 < 10
Lead content	mg/l	EN 237	max. 5 < 2
Benzene content	Vol. %	EN 238	max. 1.0 < 1.0
<i>Knock resistance</i>			
Research method (RON)		ISO 5164	min. 95
Motor method (MON)		ISO 5163	> 95 > 85

* The average values are subject to natural production fluctuations.

Health and safety information can be found on the safety data sheet.